



ZX70 FULLY RUGGED TABLET

- Qualcomm® Snapdragon™ 660, Octa-core Processor
- 7" LumiBond® Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810H and IP67 Certified
- Optional Barcode Reader and RFID Reader
- High Sensitivity GPS



Office Dock



Vehicle Dock



Specifications

Operating System

Android 9.0

Mobile Computing Platform

Qualcomm® Snapdragon™ 660, Octa-core 1.95 GHz, burst up to 2.2 GHz

VGA Controller

Qualcomm® Adreno™ 512 GPU

Display

7" IPS TFT LCD HD (1280 x 720)
LumiBond® display with Getac sunlight readable technology
Capacitive touchscreen with glove on

Storage & Memory

4GB LPDDR4
64GB storage

Keyboard

4 tablet buttons (Power, Barcode Launch Button, Volume Up, Volume Down)

Pointing Device

Touchscreen
- Capacitive multi-touch screen

Expansion Slot

MicroSD x1

I/O Interface

8M pixels webcam x 1
12M pixels auto focus rear camera x 1
MicroUSB 2.0 (Client) x 1
USB 2.0 (Host) x 1
Docking connector (Pogo/JAE)
DC in Jack x 1
Optional RF antenna pass-through for GPS and WWAN

Communication Interface

Wi-Fi 802.11ac
Bluetooth (v5.0)ⁱ
Dedicated GPS
Optional 4G LTE mobile broadband

Security Feature

Optional contactless HF RFID/NFC combo reader^{ii, iii}
Optional barcode reader

Power

AC adapter (25W, 100-240VAC, 50 / 60Hz)
Li-Ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weight

218 x 142 x 27 mm (8.58 " x 5.6" x 1.08")
762g (1.68lbs)^v

Rugged Feature

MIL-STD-810H certified and IP67 certified
6 feet drop resistant^t

Environmental Specification

Temperature^s:
- Operating: -21°C to 60°C / -6°F to 140°F
- Storage: -40°C to 71°C / -40°F to 160°F
Humidity:
- 95% RH, non-condensing

Software

Getac Settings and Google Applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play Music, Play Movies, Duo and Photos)

Accessories

Carry bag
AC adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz)
Vehicle adapter (40W 11-16V, 20-32VDC)
Capacitive stylus
Rotating hand strap with kickstand and stylus holder
Office dock
Vehicle dock
USB to RS232 converter cable
Docking connector to HDMI converter cable
Protection film
Shoulder strap
Wrist strap

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper.

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- ii 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iii HF RFID/NFC combo reader applies to US & EU.
- iv Weight and dimensions vary from configurations and optional accessories.
- v Tested by a national independent third party test lab following MIL-STD-810H.

ZX70

Fully Rugged Tablet



Docking Solutions

	Getac-made Vehicle Dock (JAE)	Havis Vehicle Dock (JAE)	Gamber-Johnson Charging Cradle (Pogo)	Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	1	--	1	--	--
Speaker	1	--	--	--	--	--
Audio Output	1	1	--	1	1	1
DC in Jack	1	1	1	1	1	1
USB	USB Host x 2	USB2.0 x 2	--	USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	1	--	1	1	1
HDMI	1	1	--	--	1	--
RF antenna connector	(WWAN, GPS)	(WWAN, GPS)	--	(WWAN, GPS)	--	--

Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel : +886 2 2785 7888
globalmarketing@getac.com | www.getac.com



Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M02Y20WWW